

TABLE OF CONTENTS

FOREWORD	iii
REFERENCES	iv
NOTICE TO USERS OF THIS PUBLICATION	v
TABLE OF CONTENTS	vii
CHAPTER 1 INTRODUCTION	
1.1 MODEL PROJECT SPECIFICATION	1.1
CHAPTER 2 DUCT PERFORMANCE CHARACTERISTICS	
2.1 FIBROUS GLASS DUCT PERFORMANCE CHARACTERISTICS	2.1
2.2 USE IN MEDICAL FACILITIES	2.2
2.3 OTHER PERFORMANCE CHARACTERISTICS	2.2
CHAPTER 3 SPECIFICATIONS AND CLOSURE	
3.1 GENERAL SPECIFICATION REQUIREMENTS	3.1
3.2 CLOSURES	3.2
CHAPTER 4 FITTINGS AND CONNECTIONS	
CHAPTER 5 REINFORCEMENT	
CHAPTER 6 HANGERS AND SUPPORTS	
APPENDIX	A.1
INDEX	I.1



TABLES

5-1	Tie Rod System Reinforcement Schedule	5.2
5-1M	Tie Rod System Reinforcement Schedule	5.3
5-2	Channel System Reinforcement Schedule	5.6
5-2M	Channel System Reinforcement Schedule	5.7
5-3	Partial Wrap-Around Reinforcement Schedule	5.8
5-3M	Partial Wrap-Around Reinforcement Schedule	5.9
6-1	Maximum Hanger Spacing By Duct Size ID	6.2
6-2	Channel Selection	6.2



FIGURES

3-1	Closures	3.4
3-2	Closures (Continued)	3.5
4-1	One-Way Transitions	4.1
4-2	Two-Way Transitions	4.2
4-3	Elbows	4.3
4-4	Offset	4.4
4-5	Tees and Branch Take Offs	4.5
4-6	90 Degree Elbows with Turning Vanes	4.6
4-7	Entry Branch and Splitter Damper	4.7
4-8	End Caps	4.8
4-9	Flange on Opening	4.9
4-10	Sheet Metal and Equipment Connection Details	4.10
4-11	Sheet Metal and Equipment Connection Details (Continued)	4.11
4-12	Register and Grille Attachment	4.12
4-13	Diffuser Connection	4.13
5-1	Tie Rod Termination Methods	5.1
5-2	Tie Rod Reinforcement	5.2
5-2M	Tie Rod Reinforcement	5.3
5-3	Tie Rod Reinforcement at Joint	5.4
5-4	Channel Reinforcement Examples—Positive Pressure	5.5
5-5	Partial Wrap-Around Reinforcement	5.8
5-6	Partial Wrap-Around Reinforcement	5.9
5-7	Channel Reinforcement—Negative Pressure Systems	5.10
5-8	Fitting Reinforcement—90 Degree Elbows	5.11
5-9	Reinforcement—90 Degree Elbows	5.12
5-10	Reinforcement—Branch Connections	5.13
5-11	Reinforcement—Tees	5.14
5-12	Reinforcement—Offsets and Mitered Elbows	5.15
5-13	Reinforcements—Transitions	5.16
5-14	Reinforcement—Access Doors	5.17
5-15	Reinforcement—End Caps	5.18
6-1	Allowable Hanger Spacing, Straight Duct, 3 in. (75 mm) Wide Channel	6.1
6-2	Hanging Duct	6.3
6-3	Hanging Duct Fittings Up to 48 in. (1.22 m) Width	6.4
6-4	Hanging Duct Fittings Up to 48 in. (1.22 mm) Width (Continued)	6.5
6-5	Vertical Riser Support	6.6
6-6	Electric Heater Support	6.7
6-7	Volume Damper Installation	6.8

